











































Welding sockets

with and without collar

SPECIFICATION

- Type A: with chamfer
- Type B: with collar

Steel ST

- weldable
- turned
- blank

INFORMATION

Welding sockets GN 7490 are used in container construction or in hydraulics for mounting instruments such as oil level sight glasses

The plane surfaces are machined, with the effect that they can be used as sealing surface in connection with a sealing element or compound.

The favourably dimensioned wall thickness prevents deformation or burn-through during welding.


Type B is used if exact positioning through the mounting bore or a low construction height is required.


ON REQUEST

- Stainless Steel-Welding sockets
- metric threads




Examples of application





Type B



*Complete with type index of the Welding sockets

Α	В		
with chamfer	with colla		

GN 7490

Description	d1	d2	d 3	h1	h2	2,7
GN 7490-ST-G1/8-*	G 1/8	20	16	10	3	18
GN 7490-ST-G1/4-*	G 1/4	24	20	14	3	35
GN 7490-ST-G3/8-*	G 3/8	28	22	14	4.5	42
GN 7490-ST-G1/2-*	G 1/2	32	26	16	4.5	57
GN 7490-ST-G3/4-*	G 3/4	40	32	18	6	97
GN 7490-ST-G1-*	G 1	50	40	20	7.5	165
GN 7490-ST-G11/4-*	G 1 1/4	60	50	22	7.5	244
GN 7490-ST-G11/2-*	G11/2	65	55	24	7.5	282

Weight A

