

SLIP/FIXED RENEWABLE BUSHINGS – CARBIDE



SFC

ID RANGE	OD	LENGTH	ANSI PART NO.	LOCK SCREW	
.0520-.0934 #55-#43 1.35-2.35mm	5/16 .3125-.3123	5/16	SFC-20-5	LS-1	
		1/2	SFC-20-8		
		3/4	SFC-20-12	RC-01	
		1	SFC-20-16		
.0935-.1562 #42-5/32 2.40-3.90mm		5/16	SFC-20-5	RK-01	
		1/2	SFC-20-8	RK-10	
		3/4	SFC-20-12		
		1	SFC-20-16		
.1406-.1889 9/64-3/16 3.60-4.75mm	1/2 .5000-.4998	5/16	SFC-32-5	LS-1	
		1/2	SFC-32-8		
		3/4	SFC-32-12	RC-01	
		1	SFC-32-16		
.1890-.3438 #12-11/32 4.80-8.70mm		5/16	SFC-32-5	RK-01	
		1/2	SFC-32-8	RK-10	
		3/4	SFC-32-12		
		1	SFC-32-16		
.2812-.5312 9/32-17/32 7.20-13.00mm	3/4 .7500-.7498	1/2	SFC-48-8	LS-1	
		3/4	SFC-48-12	RC-01	
		1	SFC-48-16	RK-01	
		1-3/8	SFC-48-22	RK-10	
.4688-.7812 15/32-25/32 12.00-19.50mm		1 1.0000-.9998	1/2	SFC-64-8	LS-2
			3/4	SFC-64-12	RC-02
			1	SFC-64-16	RK-02
			1-3/8	SFC-64-22	RK-12
	1-3/4		SFC-64-28		
.7188-1.0312 23/32 - 1-1/32 18.50-27.00mm	1-3/8 1.3750-1.3747		3/4	SFC-88-12	LS-2
			1	SFC-88-16	RC-02
			1-3/8	SFC-88-22	RK-02
		1-3/4	SFC-88-28	RK-12	
		2-1/8	SFC-88-34		
2-1/2		SFC-88-40			
.9688-1.4062 31/32 - 1-13/32 25.00-35.00mm		1-3/4 1.7500-1.7497	1	SFC-112-16	LS-3
			1-3/8	SFC-112-22	RC-03
	1-3/4		SFC-112-28	RK-03	
	2-1/8		SFC-112-34	RK-14	
	2-1/2		SFC-112-40		
3	SFC-112-48				
1.3438-1.7812 1-11/32 - 1-25/32 35.00-45.00mm	2-1/4 2.2500-2.2496		1	SFC-144-16	LS-3
			1-3/8	SFC-144-22	RC-03
		1-3/4	SFC-144-28	RK-03	
		2-1/8	SFC-144-34	RK-03	
		2-1/2	SFC-144-40		
3		SFC-144-48			

Note: Due to manufacturing requirements, head dimensions of some carbide bushings may differ slightly from ANSI standards. Most carbide bushings have steel heads.

SLIP/FIXED RENEWABLE BUSHINGS – METRIC



SFM

ID RANGE	OD	LENGTH	ANSI PART NO.	LOCK SCREW
.35-1.00mm	8mm 8.000-7.994mm	*10mm	SFM-8-10	LSM-1 LSM-2 RCM-1 RCM-2
1.01-1.80mm		*16mm	SFM-8-16	
1.81-4.00mm		10mm	SFM-8-10	
		16mm	SFM-8-16	
		10mm	SFM-8-10	
4.01-6.00mm	10mm 10.000-9.994mm	16mm	SFM-8-16	
6.01-8.00mm		12mm	SFM-10-12	
		20mm	SFM-10-20	
8.01-10.00mm	12mm 12.000-11.992mm	25mm	SFM-10-25	LSM-3 LSM-4 RCM-3 RCM-4
		12mm	SFM-12-12	
		20mm	SFM-12-20	
10.01-12.00mm	15mm 15.000-14.992mm	25mm	SFM-12-25	LSM-5 LSM-6 RCM-5 RCM-6
		16mm	SFM-15-16	
		28mm	SFM-15-28	
12.01-15.00mm	18mm 18.000-17.992mm	36mm	SFM-15-36	LSM-7 LSM-8 RCM-7 RCM-8
		16mm	SFM-18-16	
		28mm	SFM-18-28	
15.01-18.00mm	22mm 22.000-21.991mm	36mm	SFM-18-36	LSM-7 LSM-8 RCM-7 RCM-8
		20mm	SFM-22-20	
		36mm	SFM-22-36	
18.01-22.00mm	26mm 26.000-25.991mm	45mm	SFM-22-45	LSM-7 LSM-8 RCM-7 RCM-8
		20mm	SFM-26-20	
		36mm	SFM-26-36	
20.01-24.00mm	30mm 30.000-29.991mm	45mm	SFM-26-45	LSM-7 LSM-8 RCM-7 RCM-8
		25mm	SFM-30-25	
		45mm	SFM-30-45	
24.01-28.00mm	35mm 35.000-34.989mm	56mm	SFM-30-56	LSM-7 LSM-8 RCM-7 RCM-8
		25mm	SFM-35-25	
		45mm	SFM-35-45	
28.01-32.00mm	42mm 42.000-41.989mm	56mm	SFM-35-56	LSM-7 LSM-8 RCM-7 RCM-8
		30mm	SFM-42-30	
		56mm	SFM-42-56	
32.01-36.00mm	48mm 48.000-47.989mm	67mm	SFM-42-67	LSM-7 LSM-8 RCM-7 RCM-8
		30mm	SFM-48-30	
		56mm	SFM-48-56	
36.01-40.00mm	55mm 55.000-54.987mm	67mm	SFM-48-67	LSM-7 LSM-8 RCM-7 RCM-8
		30mm	SFM-55-30	
		56mm	SFM-55-56	
40.01-44.00mm	62mm 62.000-61.987mm	67mm	SFM-55-67	LSM-7 LSM-8 RCM-7 RCM-8
		35mm	SFM-62-35	
		67mm	SFM-62-67	
44.01-48.00mm	62mm 62.000-61.987mm	78mm	SFM-62-78	LSM-7 LSM-8 RCM-7 RCM-8

ID RANGE (G6)	OD (h5)	LENGTH	ANSI PART NO.	LOCK SCREW
48.01-55.00mm	70mm 70.000-69.987mm	35mm	SFM-70-35	LSM-7 LSM-8 RCM-7 RCM-8
		67mm	SFM-70-67	
		78mm	SFM-70-78	
55.01-62.00mm	78mm 78.000-77.987mm	40mm	SFM-78-40	LSM-7 LSM-8 RCM-7 RCM-8
		78mm	SFM-78-78	
		105mm	SFM-78-105	
62.01-70.00mm	85mm 85.000-84.985mm	40mm	SFM-85-40	LSM-7 LSM-8 RCM-7 RCM-8
		78mm	SFM-85-78	
		105mm	SFM-85-105	
70.01-78.00mm	95mm 95.000-94.985mm	45mm	SFM-95-45	LSM-7 LSM-8 RCM-7 RCM-8
		89mm	SFM-95-89	
		112mm	SFM-95-112	
78.01-85.00mm	105mm 105.000-104.985mm	45mm	SFM-105-45	LSM-7 LSM-8 RCM-7 RCM-8
		89mm	SFM-105-89	
		112mm	SFM-105-112	

* Small metric drill sizes through .80mm are counterbored 1.00mm diameter, with 3mm drill-bearing length.